

2018+ HONDA ACCORD 2.0T

PERFORMANCE AIR INTAKE

PARTS LIST & INSTALLATION GUIDE



PARTS INCLUDED

- 1PC** Silicone Intake Elbow
- 1PC** CNC Aluminum MAF Sensor Housing
- 1PC** High-Flow, Oiled Filter
- 1PC** Rubber MAF Housing Gasket
- 1PC** Rotational-Molded Airbox
- 4PC** Worm Gear Clamps
Mounting Hardware

TOOLS NEEDED

- 2.5mm Allen Key
- 7mm Socket
- 8mm Socket
- 10mm Socket
- 1/4" Drive Ratchet
- 1/4" Drive Extension
- Phillips Screwdriver

INSTALL TIME 30 Minutes

INSTALL DIFFICULTY

DISCLAIMER

- Raise vehicle only on jack stands or on a vehicle lift.
- Allow vehicle to cool completely prior to attempting installation.
- Do not run the engine or drive the vehicle while overheating; serious damage can occur.
- Please dispose of any liquids properly.
- Mishimoto is not responsible for any vehicle damage or personal injury due to installation errors, misuse, or removal of Mishimoto products.
- Mishimoto suggests that a trained professional install all Mishimoto products.

INSTALL PROCEDURE

1. Remove the pop-clips that secure the air duct. (4x pop-clips)

2. Lift the stock air duct to remove it along with the rubber piece at its base.



3. Before carrying out this next step, make sure the ignition is off, then you can disconnect the MAF sensor.



4. Pull down the two tabs that secure the lid on the airbox.
5. Loosen the clamp on the intake hose. Then slide it off the pipe. (1x worm gear clamp)
6. Lift the hose and airbox lid to remove them.
7. Remove the bolts that secure the base of the airbox. (2x 10mm bolts)



8. Remove the filter from the airbox. With the filter out, lift the airbox to disengage the peg at its base.

CONTINUED ON FOLLOWING PAGE

01

2018+ HONDA ACCORD 2.0T PERFORMANCE AIR INTAKE INSTALLATION GUIDE



9. Transfer the MAF sensor from the stock hose to the Mishimoto MAF housing. Use the provided hardware. (2x 2.5mm Allen bolts)



10. Transfer the grommets from the stock airbox to the Mishimoto airbox.



11. Disassemble the airbox lid. (4x 2.5mm Allen keys)
12. Place the rubber cap onto the resonator port.



13. Install the Mishimoto airbox so it engages the peg at the bottom.
14. Lower the filter into the airbox. Insert the open end through the airbox opening. Then connect the MAF housing to the filter. (1x worm gear clamp)



15. Position two clamps over the silicone coupler. Then install the silicone coupler to the MAF housing and intake tube. (2x worm gear clamps)
16. Rotate the MAF housing to avoid unnecessary stress on the sensor wiring. Connect the MAF sensor to the harness on the nearby MAF housing.
17. Tighten the clamps on your coupler to fully secure it to the housing and intake tube. (2x worm gear clamps)
18. Secure the airbox using the original hardware. (2x 10mm bolts)
19. Reinstall the air duct. (4x pop-clips)
20. Reassemble the airbox lid. (4x 2.5mm Allen bolts)

Congratulations! You have finished installing the Mishimoto 2018+ Honda Accord 2.0T Performance Air Intake.